


LED VAPOUR PROOF

CULUS FC ROHS EPISTAR

#VP-484-5



DESCRIPTION

The VP-484-5 Vapour Proof fixture is ideal for use in environments subject to high levels of moisture and dust. Its non-discolouring opal polycarbonate diffuser provides even light that is soft and comfortable. Installation options include ceiling and wall mounting, making it versatile for any application.

POPULAR APPLICATIONS








MANUFACTURING PARKING GARAGES

FOOD PROCESSING

PRODUCT DIMENSIONS



PHOTOMETRIC SPECS/ILLUMINANCE AT A DISTANCE





TECHNICAL DATA

| LIGHT SPECIFICATIONS | | |
|----------------------|------------------|--|
| Lumens | 4000 | |
| CCT | 5000K | |
| CRI | ≥83 | |
| DRIVER | | |
| Driver Type | Constant Current | |
| HOURS | | |
| Rated Hours | 50,000 | |

| ELECTRICAL | | |
|-------------------|---------------|--|
| Wattage | 40W | |
| System Watts | 40W | |
| Input Voltage | 100-277V | |
| CONSTRUCTION | | |
| Housing Material | Polycarbonate | |
| Diffuser Material | Polycarbonate | |
| IP Rating | IP65 | |
| LED CHIP | | |
| Chip Brand | EPISTAR | |
| Chip Type | SMD | |
| | | |

| TEMPERATURE | | |
|----------------------|---|--|
| Minimum Start | -40°C | |
| Ambient Temp | 50°C | |
| DIMENSIONS & WEIGHT | | |
| Dimensions | 47 ⁵³ / ₆₄ " x 2 ²⁹ / ₃₂ " x 4 ⁹ / ₁₆ " | |
| Weight | 1.9 KGS | |
| APPROVALS & LISTINGS | | |
| cUL | cETL 4008363 | |
| DLC Listed | VP-484-5 | |
| IESNA | LM-79 | |