











DESCRIPTION

The VP-484-MS-5 Vapour Proof fixture is ideal for use in environments subject to high levels of moisture and dust. Its non-discolouring opal polycarbonate diffuser provides even light that is soft and comfortable. With the added motion and daylight harvesting sensors, these fixtures are the best solution if you are looking for dependable illumination in rugged conditions that bring maximum energy savings. Installation options include ceiling and wall mounting, making it versatile for any application.

POPULAR APPLICATIONS









MANUFACTURING


FOOD PROCESSING

PRODUCT DIMENSIONS



PHOTOMETRIC SPECS/ILLUMINANCE AT A DISTANCE





TECHNICAL DATA

LIGHT SPECIFICATIONS		
Lumens	4000	
ССТ	5000K	
CRI	≥83	
DRIVER		
Driver Type	Constant Current	
HOURS		
Rated Hours	50,000	

ELECTRICAL		
Wattage	40W	
System Watts	40W	
Input Voltage	100-277V	
CONSTRUCTION		
Housing Material	Polycarbonate	
Diffuser Material	Polycarbonate	
IP Rating	IP65	
LED CHIP		
Chip Brand	EPISTAR	
Chip Type	SMD	

TEMPERATURE		
Minimum Start	-40°C	
Ambient Temp	50°C	
MOTION DETECTION		
Ceiling Detection Angle	360°	
Wall Detection Angle	150°	
DIMENSIONS & WEIGHT		
Dimensions	47 ⁵³ / ₆₄ " x 2 ²⁹ / ₃₂ " x 4 ⁹ / ₁₆ "	
Weight	1.98 KGS	
APPROVALS & LISTINGS		
cUL	cETL 4008363	
DLC Listed	VP-484-MS-5	
IESNA	LM-79	