



#### **DESCRIPTION**

Core's industry leading LED linear strips can be used in a wide variety of applications. Utilizing high quality Epistar chips, we deliver a consistent, even light output with fully dimmable capabilities in warm or natural white colours. Designed with high strength aluminum at only 0.8mm thickness, these strips are a durable, low profile solution for any project.

#### **ACCESSORIES**

## POPULAR APPLICATIONS







Power Cord LS-PCORD



**Double-ended Connector** LS-CONN2 (2') LS-CONN4 (4')



Hardwire Cord (8') LS-HW8



ACCENT/COVE LIGHTING



**UNDER CABINET** LIGHTING

# TECHNICAL SPECIFICATIONS

MODEL#	DESCRIPTION	VOLTAGE	LAMP WATTS	LUMENS	ССТ	CRI
LS9-3	4W 9" LED STRIP 3000K	120V	4W	400	3000K	≥80
LS9-4	4W 9" LED STRIP 4000K	120V	4W	400	4000K	≥80
LS12-3	4W 1-FOOT LED STRIP 3000K	120V	4W	400	3000K	≥80
LS12-4	4W 1-FOOT LED STRIP 4000K	120V	4W	400	4000K	≥80
LS24-3	7W 2-FOOT LED STRIP 3000K	120V	7W	755	3000K	≥80
LS24-4	7W 2-FOOT LED STRIP 4000K	120V	7W	755	4000K	≥80
LS36-3	12W 3-FOOT LED STRIP 3000K	120V	12W	1260	3000K	≥80
LS36-4	12W 3-FOOT LED STRIP 4000K	120V	12W	1260	4000K	≥80
LS48-3	15W 4-FOOT LED STRIP 3000K	120V	15W	1740	3000K	≥80
LS48-4	15W 4-FOOT LED STRIP 4000K	120V	15W	1740	4000K	≥80


# WHAT'S IN THE BOX

The following are included with every LS Strip unit:

- 1 x hardwire cord
- 1 x double-ended connector
- 1 x butt end
- mounting clips and screws



## PRODUCT DIMENSIONS



MODEL#	LENGTH
LS9-3/LS9-4	8.2"
LS12-3/LS12-4	11.2"
LS24-3/LS24-4	22.5"
LS36-3/LS36-4	34.5"
LS48-3/LS48-4	46.5"