



DESCRIPTION

Core's CF2 series Dimmable LED Canopy Fixture is the ultra-thin, energy-efficient solution for illuminating commercial and industrial environment. Designed better using a dropped diffuser lens, the fixture provides maximum lateral light distribution while minimzing glare. As a DLC listed Parking Garage Luminaire, it is perfect for use in parking structures, storage areas, shopping area walkways, and entryways.

MOUNTING OPTIONS



Pendant Mounting with a 3/4" conduit



Direct Surface mounting

POPULAR APPLICATIONS







LUMILEDS



STORAGE CENTERS


PARKING LOTS


GAS STATIONS

WALKWAYS

WARRANT

BOTTOM VIEW






SIDE VIEW

TOP VIEW





3.281ft	1,699.41 LUX
6.561ft	424.85 LUX
9.842ft	188.82 LUX
13.12ft	106.21 LUX
16.40ft	67.98 LUX

TECHNICAL DATA

LIGHT SPECIFICATIONS	
Lumens	4948
Efficacy	111.67 lm/W
CCT	4000K
CRI	≥82.3
Dimmable	Yes
Replaces	up to a 150W H.P.S.
DRIVER	
Brand	Inventronics
Driver Type	Constant Current
Driver Output	25-42V
HOURS	
Rated Hours	50,000

ELECTRICAL		
Wattage	45W	
System Watts	44.59W	
Input Voltage	100-277V	
Power Factor	0.9237	
THD	10.52%	
CONSTRUCTION		
Housing Material	Alloy Aluminum	
Lens Material	Polycarbonate Drop Lens	
Finish & Color	Bronze	
IP Rating	IP65	

LED CHIP		
Chip Brand	PHILIPS LUMILEDS	
Chip Type	SMD 3030	
TEMPERATURE		
Minimum Start	-40°C / -40°F	
Ambient Temp	40°C / 104°F	
DIMENSIONS & WEIGHT		
Dimensions	10" x 10" x 3 ⁵ / ₈ "	
Weight	3.0 KGS	
APPROVALS & LISTINGS		
cUL	IFAM7.E473127	
DLC Listed	PTZMD5QA	
IESNA	LM-79	