

LED FLOOD LIGHT

150W / 100-277V

#FL2-1504YK-1



DESCRIPTION

This FL2 series flood light is the latest addition to our commercial LED flood light collection. Utilizing world-leading Lumileds chips and being DLC 4.1 listed, it is the most reliable and efficient fixture available on the market. Available in multiple mounting options including yoke mount and slip fitter, this is the fixture of choice for jobs that require installing lights on walls or poles to illuminate building perimeters, walkways, and landscapes.

POPULAR APPLICATIONS










BUILDING PERIMETERS


WALKWAYS

EXTERIOR WALLS

PARKING LOTS

PRODUCT DIMENSIONS / PHOTOMETRIC SPECS / ILLUMINANCE AT A DISTANCE





3.281ft	6,289.64 LUX
6.561ft	1,572.41 LUX
9.842ft	698.85 LUX
13.12ft	393.10 LUX
16.40ft	251.59 LUX

TECHNICAL DATA

LIGHT SPECIF	ICATIONS
Lumens	18,486
Efficacy	120.67 lm/W
CCT	4000K
CRI	≥82.3
Replaces	up to 750W Metal Halide / High Pressure Sodium
DRIVER	
Brand	Inventronics
Driver Type	Constant Current
Driver Output	27-34V
HOURS	
Rated Hours	50,000

ELECTRICAL	
Wattage	150W
System Watts	153.2W
Input Voltage	100-277V
THD	<7%
Power Factor	0.93
CONSTRUCTIO	N
Housing Material	Aluminum Alloy
Housing Material Lens Material	Aluminum Alloy Polycarbonate Drop Lens
Lens Material	Polycarbonate Drop Lens
Lens Material IP Rating	Polycarbonate Drop Lens

TEMPERATUR	-40°C
winimum Start	-40°C
Ambient Temp	40°C
DIMENSIONS	& WEIGHT
Dimensions	12 ⁵ / ₈ " x 11 ³ / ₈ " x 3 ⁷ / ₁₆ "
Weight	5.2 KGS
APPROVALS	& LISTINGS
cUL	IFAM7.E473127
DLC Listed	PG4Y5FJE
IESNA	LM-79 & LM-80
NEMA	Type 7