













DESCRIPTION

This FL2 series flood light is the latest addition to our commercial LED flood light collection. Utilizing world-leading Lumileds chips and being DLC 4.1 listed, it is the most reliable and efficient fixture available on the market. Available in multiple mounting options including yoke mount and slip fitter, this is the fixture of choice for jobs that require installing lights on walls or poles to illuminate building perimeters, walkways, and landscapes.

POPULAR APPLICATIONS










BUILDING PERIMETERS


WALKWAYS

EXTERIOR WALLS

PARKING LOTS

PRODUCT DIMENSIONS / PHOTOMETRIC SPECS / ILLUMINANCE AT A DISTANCE







TECHNICAL DATA

LIGHT SPECIFI	CATIONS
Lumens	27,582
Efficacy	124.98 lm/W
CCT	4000K
CRI	≥82.1
Replaces	up to 1000W Metal Halide / High Pressure Sodium
DRIVER	
Brand	Inventronics
Driver Type	Constant Current
Driver Output	32-40V
HOURS	
Rated Hours	50,000

ELECTRICAL	
Wattage	220W
System Watts	220.7W
Input Voltage	277-480V
THD	<12%
Power Factor	0.96
CONSTRUCTIO	N
Housing Material	Aluminum Alloy
Lens Material	Polycarbonate Drop Lens
IP Rating	IP65
LED CHIP	
Chip Brand	LUMILEDS
Chip Type	SMD 3030

TEMPERATUR	-40°C
Ambient Temp	40°C
DIMENSIONS	& WEIGHT
Dimensions	12 ⁵ / ₈ " x 16 ¹⁵ / ₁₆ "
Weight	10.8 KGS
APPROVALS	& LISTINGS
cUL	IFAM7.E473127
DLC Listed	PEUTNZTX
IESNA	LM-79 & LM-80
NEMA	Type 7