



IP 65 RATED
made for outdoor environments



PHOTOCELL COMPATIBLE
provides maximum energy savings



LUMILEDS LED CHIPS
means long-lasting 50,000 hour life



10 WATTS
with a powerful 929 lumens output



TRUNNION MOUNT
provides versatile adjustability



EXTREME TEMPERATURE RANGE
operates in -35°C weather



10 YEAR WARRANTY

DESCRIPTION

The FL3 Series is a line of compact sized, minimal footprint LED Flood Lights that utilizes world-leading LED chips and drivers to deliver the most reliable fixture available on the market. They are the best solution when you are looking to install lighting fixtures on high walls or poles to illuminate building perimeters, walkways, and landscapes.

POPULAR APPLICATIONS



BUILDING PERIMETERS



WALKWAYS




EXTERIOR WALLS






PARKING LOTS

PRODUCT DIMENSIONS / PHOTOMETRIC SPECS / ILLUMINANCE AT A DISTANCE

FRONT VIEW



SIDE VIEW



TECHNICAL DATA

LIGHT SPECIFICATIONS

Lumens	929
Efficacy	89 lumens/W
CCT	4000K
CRI	≥83
Beam Angle	105°

DRIVER

Brand	Lishunda
Driver Type	Constant Current

HOURS

Rated Hours	50,000
-------------	---------------

ELECTRICAL

Wattage	10W
System Watts	10.44W
Input Voltage	100-277V
THD	<24%
Power Factor	0.8955

CONSTRUCTION

Housing Material	Aluminum
Lens Material	Glass
IP Rating	IP65
Mount Type	Trunnion

LED CHIP

Chip Brand	PHILIPS LUMILEDS
Chip Type	LUXEON 3030 2D

TEMPERATURE

Minimum Start	-35°C
Ambient Temp	50°C

DIMENSIONS & WEIGHT

Dimensions	4 41/64" x 7 3/64" x 2 19/32"
Weight	0.67 KGS

APPROVALS & LISTINGS

cETL	YES
DLC Listed	PBP5867G