



FL4-SERIES MULTI-MOUNT FLOOD LIGHT



Project	
Date	
Prepared by	
Model #	FL4-4504T5-1

OVERVIEW

The FL4-Series Flood Light represents our entry into specification grade exterior lighting. Finished in black, its sleek design and larger housing size provides an attractive look, especially when mounted on poles. Offering a wide range of mounting options, lumen packages, IES beam distribution patterns, and integrated controls, they will allow you to achieve any design requirement.

PRODUCT HIGHLIGHTS

- Interchangeable mounting options to adapt to any application: yoke, trunnion, slip fitter or mounting arm*
- Operates in -40°F/-40°C degree outdoor weather
- 1-10V dimming for maximum control and energy savings
- IP65 and Wet Location rated
- Black contemporary finish to complement all outdoor environments
- Available with integrated motion sensor or photocell (optional)

*Fixture does not include mount. Mount must be ordered separately.


OPTICAL SPECIFICATIONS

Lumen Output (lm) ₁	60826 lm	Beam Angle (°) ₁	Type V (125°x160°)
CCT (K) ₁	4000K	Projected Lifetime (L ₇₀)	50,000 hrs]
CRI (Ra) ₁	80	Chromaticity Shift	±250K
Efficacy (lm/W) ₁	135 lm/W		

ELECTRICAL SPECIFICATIONS

Power	450W	Replacement For	Up to 1000W HID or HPS/MH
Apparent Power (VA)	452.3VA	Current Draw at 120V _{AC} (A) ₂	3.8A
System Wattage (W)	449.14W	Current Draw at 208V _{AC} (A) ₂	2.1A
Input Voltage	100-277VAC	Current Draw at 240V _{AC} (A) ₂	1.9A
Output Voltage (VDC)	56VDC	Current Draw at 277V _{AC} (A) ₂	1.65A

PRODUCT DIMENSIONS



CONSTRUCTION

Housing Material	Aluminum Alloy	Installation Method	Wall Mounted/ Square Pole Mounted/ Round Pole Mounted
Housing Color	Black	Operation Range (°F/°C)	-40°F to 113°F/-40°C to 45°C
Lens Material	Polycarbonate	Weight (Kg/Lbs)	13.2kg / 29.1lbs
Dimensions (inch/mm)	27.7" x 13.3" x 3.7" / 690mm x 339mm x 95mm	Warranty	10 Years


APPROVALS AND LISTINGS

DLC Premium	PS91BRA3	IP Rating	IP65
Wet Location Rated	Yes	EPA Rating	2.57ft²
UL/ETL	cETLus	BUG Rating	B5-U3-G5

LED AND DRIVER SPECIFICATIONS

LED Type	3030	Surge Protection	L/N-PE: 10KV, L-N: 6KV
Dimmable	Yes (1-10V)	Inrush Current (A)	50A
Power Factor	0.9	Driver Class	Class 2
THD	15%		

PHOTOMETRICS



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	5,419.9	8.9%	8.9%
0-40	11,240.3	18.5%	18.5%
0-60	35,730.5	58.7%	58.7%
60-90	24,839.6	40.8%	40.8%
70-100	8,303.1	13.7%	13.7%
90-120	135.7	0.2%	0.2%
0-90	60,570.1	99.6%	99.6%
90-180	254.7	0.4%	0.4%
0-180	60,824.9	100%	100%

LCS TABLE

BUG RATING	B5 - U3 - G5	
FORWARD LIGHT	LUMENS	LUMENS %
LOW(0-30):	2,742.7	4.5%
MEDIUM(30-60):	15,582.5	25.6%
HIGH(60-80):	12,062.0	19.8%
VERY HIGH(80-90):	400.1	0.7%
BACK LIGHT		
LOW(0-30):	2,676.6	4.4%
MEDIUM(30-60):	14,731.3	24.2%
HIGH(60-80):	11,981.4	19.7%
VERY HIGH(80-90):	394.7	0.6%
UPLIGHT		
LOW(90-100):	45.2	0.1%
HIGH(100-180):	209.5	0.3%
TRAPPED LIGHT:	0.1	0%

ILLUMINANCE AT A DISTANCE

HEIGHT(FT)	CENTER BEAM	BEAM SPREAD(FT)		FIELD SPREAD(FT)	
	FOOTCANDLE	HORIZONTAL	VERTICAL	HORIZONTAL	VERTICAL
4.00	346.50 FC	11.5	24.0	19.6	44.7
8.00	86.62 FC	23.1	48.0	39.1	89.4
12.00	38.50 FC	34.6	72.0	58.7	134.1
16.00	21.66 FC	46.1	96.0	78.2	178.8
20.00	13.86 FC	57.7	120.0	97.8	223.4
		BEAM ANGLE		FIELD ANGLE	
		110.5°	143.1°	135.5°	159.7°

MOUNTING OPTIONS					
	FL-MA4	Mounting Arm for FL4-Series Area/Flood Lights		FL-SF4	Slip Fitter for FL4-Series Area/Flood Lights
	FL-TR4	Trunnion Mount for FL4-Series Area/Flood Lights		FL-YK4	Yoke Mount for FL4-Series Area/Flood Lights
ACCESSORIES					
	PC1-TPT-1	Stem Mount Swivel Photocell (Compatible with Mounting Arm or Slip Fitter option only)		FL-SHIELD34	Glare Shield for FL4-Series Area/Flood Lights (450W model only)
PRODUCT KEY					

FL4

Product Series

-

Wattage

☐ 80
☐ 100
☐ 150
☐ 200
☐ 240
☐ 300
☐ 450

CCT

☐ 4 - 4000K

LENS

☐ T3 - Type III Distribution
☐ T4 - Type IV Distribution
☐ T5 - Type V Distribution

-

Voltage

☐ 1 - 100-277V
☐ 2 - 277-480V

-

Adders

Example

FL4-2404T3-1-M6P1

FACTORY INSTALLED ADDERS

Motion Sensor Adders

☐ M6 Microwave Motion Sensor, Dimmable, 120-277V (80W-300W models)
☐ M7 Microwave Motion Sensor, Dimmable, 120-277V (450W model)

Photocell Sensor Adders

☐ P1 Stem Mount Photocell, 120V (Mounting Arm and Slip Fitter Only)