MULTI CCT

MULTI WATTAGE

RENO SMART

eco R

HELIOS SERIES
LED WRAP AROUND

DESCRIPTION

The Helios series embraces a minimalist design while providing a wide array of features making this fixture adaptable to any indoor application. Utilize the colour and wattage selections built into the fixture to create the perfect look. Easy to install and built to last, this series is sure to impress.

FEATURES

- DLC premium for the Stairwell and Passageway Luminaires
- Dual Voltage 120-347V
- 0-10V Continuous Dimming
- Surface or Suspension Mounting options
- Easy and Safe Installation
- Frosted PMMA Lens
- Rated Lifetime L70(hrs): >70,000
- Operation temperature: -13°F to 104°F (-25°C to 40°C)
- Suitable for Damp Locations
- Includes Coverplate and V-Hangers
- CRI >80
- 5 year warranty

APPLICATIONS

- Corridors
- Education Facilities
- Low Bay Application
- Multi-res/Retirement

DLC LISTED

DLC LISTED PREMIUM

UL CERTIFIED

DUAL VOLTAGE 120-347V

MULTI CCT

MULTI POWER

DAMP

5 YR WARRANTY

SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	SIZE	LUMENS	EFFICACY	CRI
R38005	RENO-HWR2-DV-MW-MCCT-ECO	15W	120-347V	3500K	2FT	2097 lm	139.8 lm/W	>80
		20W				2796 lm		
		25W				3495 lm		
		15W		4000K		2226 lm	148.4 lm/W	
		20W				2968 lm		
		25W				3710 lm		
		15W		5000K		2137.5 lm	142.5 lm/W	
		20W				2850 lm		
		25W				3562.5 lm		
R38011	RENO-HWR4-DV-MW-MCCT-ECO	30W	120-347V	3500K	4FT	4194 lm	139.8 lm/W	>80
		40W				5592 lm		
		50W				6990 lm		
		30W		4000K		4452 lm	148.4 lm/W	
		40W				5936 lm		
		50W				7420 lm		
		30W		5000K		4275 lm	142.5 lm/W	
		40W				5700 lm		
		50W				7125 lm		

DLC INFORMATION

ORDER#	MODEL#	APPLICATION	DLC	
			STANDARD	PREMIUM
R38005	RENO-HWR2-DV-MW-MCCT-ECO	Direct Linear Ambient Luminaires	S-KGQD97	-
		Stairwell and Passageway Luminaires	-	S-CSQ3M9
R38011	RENO-HWR4-DV-MW-MCCT-ECO	Direct Linear Ambient Luminaires	S-6S9FTK	-
		Stairwell and Passageway Luminaires	-	S-7LQC69

ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R39204	RENO-RP	LED suspension kit
R83004	RENO-EM-C08	Emergency LED Driver

RENO-RP

RENO-EM-C08

RENO SMART NLC SYSTEM ACCESSORIES

ORDER#	MODEL#	DESCRIPTION
R75001	RENO-RS-JK-BPDN-12V	Bluetooth 3.5mm Jack PIR Sensor for RENO Smart NLC System
R75002	RENO-RS-JK-BMWM-12V	Bluetooth 3.5mm Jack Microwave Sensor for RENO Smart NLC System
R75102*	RENO-RS-JK-AD-L	Adjustable "L" Angle Adaptor for 3.5mm Jack Sensors
R75201	RENO-RS-GW-BCNW	Ceiling Mounted Gateway for RENO Smart NLC System
R75302	RENO-RS-RC-BNNG	7-Key Smart Wall Switch for RENO Smart NLC System
R75301	RENO-RS-RC-BNNN	5-Key Reset Remote (*Requires R75102)

RENO-RS-JK-BPDN-12V   **RENO-RS-JK-BMWM-12V**   **RENO-RS-JK-AD-L**   **RENO-RS-GW-BCNW**

RENO-RS-RC-BNNG   **RENO-RS-RC-BNNN**

REV. 11/20/24

STANDALONE SENSOR

ORDER#	MODEL#	DESCRIPTION
R74002	RENO-SENSOR-PIR-H-EX	For external mounting when installed above 13FT

RENO-SENSOR-PIR-H-EX

STANDALONE SENSOR REMOTES

ORDER#	MODEL#	DESCRIPTION
R73002	RENO-REMOTE-H	Controller for Bi-Level Sensor (with screen)
R73005	RENO-REMOTE-H-ECO	Remote Control for ECO LINEAR HIGHBAY/FULL CUTOFF WALLPACK/ LINEAR STRIP/VP FIXTURE (without screen)

RENO-REMOTE-H

RENO-REMOTE-H-ECO

DIMENSIONS

2FT.

97mm
(3.8")

610mm
(24.0")

132mm
(5.2")

4FT.

97mm
(3")

1219mm
(48")

132mm
(5.2")